

**2014 OSSC CHAPTER 10 - MEANS OF EGRESS  
TABLE OF CONTENTS**

**Section 1001 ADMINISTRATIVE**

- 1001.1 General
- 1001.2 Alterations to existing means of egress
- 1001.3 Maintenance
- 1001.4 Fire safety and evacuation plans

**Section 1002 DEFINITIONS**

**Section 1003 GENERAL MEANS OF EGRESS**

- 1003.1 Applicability
- 1003.2 Ceiling Height
- 1003.3 Protruding Objects
  - .3.1 Headroom
  - .3.2 Post mounted objects
  - .3.3 Horizontal projections
  - .3.4 Clear width
- 1003.4 Floor Surface
- 1003.5 Elevation Change
- 1003.6 Means of Egress Continuity
- 1003.7 Elevators, Escalators and Moving Walks

**Section 1004 OCCUPANT LOAD**

- 1004.1 Design Occupant Load
  - .1.1 Cumulative occupant loads
    - .1.1.1 Intervening spaces
    - .1.1.2 Adjacent levels
  - .1.2 Areas without fixed seating

*Table 1004.1.2 Max Floor Area Allow. Per Occupant*

- 1004.2 Increased Occupant Load
- 1004.3 Posting of Occupant Load
- 1004.4 Fixed seating
- 1004.5 Outdoor areas
- 1004.6 Multiple Occupancies

**Section 1005 MEANS OF EGRESS SIZING**

- 1005.1 General
- 1005.2 Minimum width based on component
- 1005.3 Required capacity based on occupant load
  - .3.1 Stairways
  - .3.2 Other egress components
- 1005.4 Continuity
- 1005.5 Distribution of egress capacity
- 1005.6 Egress convergence
- 1005.7 Encroachment
  - .7.1 Doors
  - .7.2 Other projections
  - .7.3 Protruding objects

**Section 1006 MEANS OF EGRESS ILLUMINATION**

- 1006.1 Illumination Required
- 1006.2 Illumination Level
- 1006.3 Emergency Power for Illumination
  - .3.1 Illumination level under emergency power

**Section 1007 ACCESSIBLE MEANS OF EGRESS**

- 1007.1 Accessible means of egress required
- 1007.2 Continuity and components
  - .2.1 Elevators required
- 1007.3 Stairways
- 1007.4 Elevators
- 1007.5 Platform lifts
  - .5.1 Openness
- 1007.6 Areas of refuge
  - .6.1 Size
  - .6.2 Separation
  - .6.3 Two-way communication
- 1007.7 Exterior area for assisted rescue
  - .7.1 Level of exit discharge
  - .7.2 Outdoor facilities
  - .7.3 Size
  - .7.4 Separation
  - .7.5 Openness
  - .7.6 Stairway
  - .7.8 Two-way communication
    - .7.8.1 System requirements
    - .7.8.2 Directions
- 1007.9 Signage
- 1007.10 Directional signage
- 1007.11 Instructions

**Section 1008 DOORS, GATES & TURNSTILES**

- 1008.1 Doors
  - .1.1 Size of doors
    - .1.1.1 Projections into clear width
  - .1.2 Door Swing
  - .1.3 Door opening force
    - .1.3.1 Location of applied forces
  - .1.4 Special doors
    - .1.4.1 Revolving doors
      - Table 1008.1.4.1 Revolving Door Speeds*
        - .1.4.1.1 Egress component
        - .1.4.1.2 Other than egress component
    - .1.4.2 Power-operated doors
    - .1.4.3 Horizontal sliding doors
    - .1.4.4 Security grilles
  - .1.5 Floor elevation
  - .1.6 Landings at doors
  - .1.7 Thresholds
  - .1.8 Door arrangement
  - .1.9 Door operations
    - .1.9.1 Hardware
    - .1.9.2 Hardware height
    - .1.9.3 Locks and latches
    - .1.9.4 Bolt locks
    - .1.9.5 Unlatching
      - .1.9.5.1 Closet and bathroom doors in Group R-4 occupancies

- .1.9.6 Special locking arrangements in Group I-1, I-2, R-3 and R-4 facilities providing care
- .1.9.7 Delayed egress locks
- .1.9.8 Access-Controlled egress doors
- .1.9.9 Electromagnetically locked egress doors
- .1.9.10 Locking arrangements in correctional facilities
- .1.9.11 Stairway doors
- 1008.1.10 Panic and fire exit hardware
  - .1.10.1 Installation
  - .1.10.2 Balanced doors
- 1008.2 Gates
  - .2.1 Stadiums
- 1008.3 Turnstiles
  - .3.1 High turnstile
  - .3.2 Additional door

### **Section 1009 STAIRWAYS**

- 1009.1 General
- 1009.2 Interior exit stairways
  - .2.1 Where required
  - .2.2 Enclosure
- 1009.3 Exit access stairways
  - .3.1 Construction
    - .3.1.1 Materials
    - .3.1.2 Fire-resistance rating
    - .3.1.3 Continuity
    - .3.1.4 Openings
      - .3.1.4.1 Prohibited openings
    - .3.1.5 Penetrations
      - .3.1.5.1 Prohibited penetrations
    - .3.1.6 Joints
    - .3.1.7 Ducts and air transfer openings
    - .3.1.8 Exterior walls
- 1009.4 Width
- 1009.5 Headroom
- 1009.6 Walkline
- 1009.7 Stair treads and risers
  - .7.1 Dimension reference surfaces
  - .7.2 Riser height and tread depth
  - .7.3 Winder treads
  - .7.4 Dimensional uniformity
  - .7.5 Nosing and riser profile
    - .7.5.1 Nosing projection size
    - .7.5.2 Nosing projection uniformity
    - .7.5.3 Solid risers
- 1009.8 Stairway landings
- 1009.9 Stairway construction
  - .9.1 Stairway walking surface
  - .9.2 Outdoor conditions
  - .9.3 Enclosures under interior stairways
  - .9.4 Enclosures under exterior stairways
- 1009.10 Vertical rise
- 1009.11 Curved stairways
- 1009.12 Spiral stairways
- 1009.13 Alternating tread devices
  - .13.1 Handrails of alternating tread devices
  - .13.2 Treads of alternating tread devices

- 1009.14 Ship ladders
- 1009.15 Handrails
- 1009.16 Stairway to roof
  - .16.1 Roof access
  - .16.2 Protection at roof hatch openings
- 1009.17 Stairway to elevator equipment

### **Section 1010 Ramps**

- 1010.1 Scope
- 1010.2 Enclosure
- 1010.3 Slope
- 1010.4 Cross slope
- 1010.5 Vertical rise
- 1010.6 Minimum dimensions
  - .6.1 Width
  - .6.2 Headroom
  - .6.3 Restrictions
- 1010.7 Landings
  - .7.1 Slope
  - .7.2 Width
  - .7.3 Length
  - .7.4 Change in direction
  - .7.5 Doorways
- 1010.8 Ramp construction
  - .8.1 Ramp surface
  - .8.2 Outdoor conditions
- 1010.9 Handrails
- 1010.10 Edge protections
  - .10.1 Curb, rail, wall or barrier
  - .10.2 Extended floor or ground surface
- 1010.11 Guards

### **Section 1011 EXIT SIGNS**

- 1011.1 Where Required
- 1011.2 Floor-level exit signs in Group R-1
- 1011.3 Illumination
- 1011.4 Raised character and Braille Exit Signs
- 1011.5 Internally Illuminated Exit Signs
- 1011.6 Externally Illuminated Exit Signs
  - .6.1 Graphics
  - .6.2 Exit sign illumination
  - .6.3 Power source

### **Section 1012 HANDRAILS**

- 1012.1 Where Required
- 1012.2 Height
- 1012.3 Handrail graspability
  - .3.1 Type I
  - .3.2 Type II
- 1012.4 Continuity
- 1012.5 Fittings
- 1012.6 Handrail extensions
- 1012.7 Clearance
- 1012.8 Projections
- 1012.9 Intermediate handrails

## **Section 1013 GUARDS**

- 1013.1 General
- 1013.2 Where Required
  - .2.1 Glazing
- 1013.3 Height
- 1013.4 Opening Limitations
- 1013.5 Screen Porches
- 1013.6 Mechanical Equipment
- 1013.7 Roof Access
- 1013.8 Window sills
  - .8.1 Window opening control devices

## **Section 1014 EXIT ACCESS**

- 1014.1 General
  - 1014.2 Egress Through Intervening Spaces
    - .2.1 Multiple tenants
  - 1014.3 Common Path of Egress Travel
- Table 1014.3 Common Path of Egress Travel*

## **Section 1015 EXIT AND EXIT ACCESS DOORWAYS**

- 1015.1 Exit or exit access doorways from spaces
- Table 1015.1 Spaces With One Exit or Exit Access Doorway*
- .1.1 Three or more exits or exit access doorways
- 1015.2 Exit or Exit Access Doorway Arrangement
    - .2.1 Two exits or exit access doorways
    - .2.2 Three or more exits or exit access doorways
  - 1015.3 Boiler, Incinerator, and Furnace Rooms
  - 1015.4 Refrigeration Machinery Rooms
  - 1015.5 Refrigerated Rooms or Spaces
  - 1015.6 Daycare Means of Egress

## **Section 1016 EXIT ACCESS TRAVEL DISTANCE**

- 1016.1 General
  - 1016.2 Limitations
    - .2.1 Exterior egress balcony increase
  - 1016.3 Measurement
- Table 1016.2 Exit Access Travel Distance*
- 3.1 Exit access stairways and ramps

## **Section 1017 AISLES**

- 1017.1 General
- 1017.2 Aisles in assembly spaces
- 1017.3 Aisles in Groups B and M
- 1017.4 Aisle accessways in Group M
- 1017.5 Aisles in other than assembly spaces and Groups B & M

## **Section 1018 CORRIDORS**

- 1018.1 Construction
- Table 1018.1 Corridor Fire-Resistance Rating*
- 1018.2 Width
- Table 1018.2 Minimum Corridor Width*
- 1018.3 Obstruction
  - 1018.4 Dead ends
  - 1018.5 Air movement in corridors
    - .5.1 Corridor ceiling
  - 1018.6 Corridor Continuity

## **Section 1019 EGRESS BALCONIES**

- 1019.1 General
- 1019.2 Wall separation
- 1019.3 Openness
- 1019.4 Location

## **Section 1020 EXITS**

- 1020.1 General
- 1020.2 Exterior Exit Doors
  - .2.1 Detailed requirements
  - .2.2 Arrangement

## **Section 1021 NUMBER OF EXITS AND EXIT CONFIGURATION**

- 1021.1 General
  - 1021.2 Exits from stories
    - .2.1 Mixed occupancies
- Table 1021.2(1) Stories with one exit or access to one exit for R-2 occupancies*
- Table 1021.2(2) Stories with one exit or access to one exit for other occupancies*
- .2.2 Basements
  - .2.3 Single-story or multiple-story dwelling units
  - .2.4 Three or more exits
  - .2.5 Additional exits
- 1021.3 Exit configuration
    - .3.1 Access to exits at adjacent levels
  - 1021.4 Vehicular ramps

## **Section 1022 INTERIOR EXIT STAIRWAYS AND RAMPS**

- 1022.1 General
- 1022.2 Construction
- 1022.3 Termination
  - .3.1 Extension
- 1022.4 Openings
- 1022.5 Penetrations
- 1022.6 Ventilation
- 1022.7 Interior exit stairway and ramp exterior walls
- 1022.8 Discharge identification
- 1022.9 Stairway identification signs
  - .9.1 Signage requirements
- 1022.10 Smokeproof enclosures and pressurized stairways and ramps
  - .10.1 Termination and extension
  - .10.2 Enclosure access

## **Section 1023 EXIT PASSAGEWAYS**

- 1023.1 Exit Passageways
- 1023.2 Width
- 1023.3 Construction
- 1023.4 Termination
- 1023.5 Openings and Penetrations
- 1023.6 Penetrations

## **Section 1024 LUMINOUS EGRESS PATH MARKINGS**

- 1024.1 General
- 1024.2 Markings within exit components
  - .2.1 Steps
  - .2.2 Landings
  - .2.3 Handrails
  - .2.4 Perimeter demarcation lines
    - .2.4.1 Floor mounted demarcation lines
    - .2.4.2 Wall mounted demarcation lines
    - .2.4.3 Transition
  - .2.5 Obstacles
  - .2.6 Doors within the exit path
    - .2.6.1 Emergency exit symbol
    - .2.6.2 Door hardware markings
    - .2.6.3 Door frame markings
- 1024.3 Uniformity
- 1024.4 Self-luminous and photoluminescent
- 1024.5 Illumination

## **Section 1025 HORIZONTAL EXITS**

- 1025.1 Horizontal Exits
- 1025.2 Separation
- 1025.3 Opening Protectives
- 1025.4 Capacity of Refuge Area

## **Section 1026 EXTERIOR EXIT STAIRWAYS AND RAMPS**

- 1026.1 Exterior Exit Stairways and Ramps
- 1026.2 Use in a Means of Egress
- 1026.3 Open Side
- 1026.4 Side Yards
- 1026.5 Location
- 1026.6 Exterior Stairway and Ramp Protection

## **Section 1027 EXIT DISCHARGE**

- 1027.1 General
- 1027.2 Exit Discharge Capacity
- 1027.3 Exit Discharge Components
- 1027.4 Egress Courts
  - .4.1 Width
  - .4.2 Construction and openings
- 1027.5 Access to a Public Way

## **Section 1028 ASSEMBLY**

- 1028.1 General
  - .1.1 Bleachers
    - .1.1.1 Spaces under grandstands and bleachers
- 1028.2 Assembly Main Exit
- 1028.3 Assembly Other Exits
- 1028.4 Foyers and Lobbies
- 1028.5 Interior Balcony and Gallery Means of Egress
- 1028.6 Width of Means of Egress For Assembly
  - .6.1 Without smoke protection

- .6.2 Smoke-protected seating
- Table 1028.6.2 Width of Aisles For Smoke-Protected Assembly*
- .6.2.1 Smoke control
- .6.2.2 Roof height
- .6.2.3 Automatic sprinklers
- .6.3 Width of means of egress for outdoor smoke-protected assembly
- 1028.7 Travel Distance
- 1028.8 Common Path of Egress Travel
  - .8.1 Path through adjacent row
- 1028.9 Assembly Aisles Are Required
  - .9.1 Minimum aisle width
  - .9.2 Aisle width
  - .9.3 Converging aisles
  - .9.4 Uniform width
  - .9.5 Assembly aisle termination
  - .9.6 Assembly aisle obstructions
- 1028.10 Aisle accessways
  - .10.1 Seating at tables
    - .10.1.1 Aisle accessway width for seating at tables
    - .10.1.2 Seating at table aisle accessway length
  - .10.2 Clear width of aisle accessways serving seating in rows
    - .10.2.1 Dual access
    - Table 1028.10.1 Smoke-Protected Assembly Aisle Accessways*
    - .10.2.2 Single access
- 1028.11 Assembly Aisle Walking Surfaces
  - .11.1 Treads
  - .11.2 Risers
  - .11.3 Tread contrasting marking stripe
- 1028.12 Seat Stability
- 1028.13 Handrails
  - .13.1 Discontinuous handrails
  - .13.2 Intermediate handrails
- 1028.14 Assembly Guards
  - .14.1 Cross Aisles
  - .14.2 Sightline-constrained guard heights
  - .14.3 Guards at the end of aisles

## **Section 1029 EMERGENCY ESCAPE & RESCUE**

- 1029.1 General
- 1029.2 Minimum Size
  - .2.1 Minimum dimensions
- 1029.3 Maximum Height From Floor
- 1029.4 Operational Constraints
- 1029.5 Window Wells
  - .5.1 Minimum size
  - .5.2 Ladders or steps

*Feel free to distribute.*

*Please notify Robert Rice of any corrections at [structdesigner@yahoo.com](mailto:structdesigner@yahoo.com)*

